



US006009062A

United States Patent [19]
Nashimoto et al.

[11] **Patent Number:** **6,009,062**
[45] **Date of Patent:** **Dec. 28, 1999**

[54] **DISC PLAYER FOR MINIDISC AND COMPACT DISC PLAYBACK**

7-296499 11/1995 Japan .

[75] Inventors: **Hiroaki Nashimoto**, Maebashi;
Masaya Nawata; **Shoji Morioka**, both
of Gunma-Gun, all of Japan

Primary Examiner—Allen T. Cao

Attorney, Agent, or Firm—Jacobson, Price, Holman &
Stern, PLLC

[73] Assignee: **Victor Company of Japan, Ltd.**,
Yokohama, Japan

[57] **ABSTRACT**

A disc player for use in playback of both a minidisc and a compact disc is formed with an opening formed on a panel for loading a minidisc and another opening formed on the panel for loading a compact disc. A chassis is provided in an orthogonal direction with respect to the panel. Mounted on the chassis is a turning frame that is horizontally turnable on the chassis. Provided on the turning frame are a rotary unit for rotating the minidisc and another rotary unit for rotating the compact disc. The turning frame is turned horizontally to move at least either the rotary units to a predetermined information reading position. The disc player has a first and a second turntable (rotary unit) on which the minidisc and the compact disc are loaded, respectively, by a loading mechanism. The loading mechanism has a first roller to transfer the compact disc and a second roller the minidisc. The second roller is provided as parallel to the first roller and within a lateral length of the first roller. The minidisc is held by a holder provided as close to the first turntable from the second roller. The first and second rollers are rotated by one actuator.

[21] Appl. No.: **09/090,254**

[22] Filed: **Jun. 4, 1998**

[30] **Foreign Application Priority Data**

Jun. 4, 1997 [JP] Japan 9-146726

[51] **Int. Cl.⁶** **G11B 33/02**

[52] **U.S. Cl.** **369/77.2**

[58] **Field of Search** 369/77.1–77.2,
369/75.1–75.2

[56] **References Cited**


U.S. PATENT DOCUMENTS

4,575,836 3/1986 Seto 369/265
5,539,717 7/1996 Choi 369/75.2
5,572,498 11/1996 Choi 369/77.2

FOREIGN PATENT DOCUMENTS

0779617 6/1997 European Pat. Off. .

10 Claims, 16 Drawing Sheets






FIG. 1A
(PRIOR ART)




FIG. 1B
(PRIOR ART)





FIG. 2






FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B







FIG. 6








FIG. 10




FIG. 11




FIG. 12




FIG. 13C




FIG. 13B












FIG. 13A








FIG. 16C




FIG. 16B






FIG. 16A



DISC PLAYER FOR MINIDISC AND COMPACT DISC PLAYBACK

BACKGROUND OF THE INVENTION

The present invention relates to a disc player for use in playback of both a minidisc (MiniDisc, MD) and a compact disc (Compact Disc, CD).

FIGS. 1A and 1B show arrangement of a minidisc and a compact disc on a conventional disc player for use in playback of both a minidisc and a compact disc.

In FIG. 1A, a minidisc 100 and a compact disc 101 are arranged side by side on one and the same plane. Reference numeral 100a designates a center hole of the minidisc 100; 100b a shutter of the minidisc 100; 100c a housing of the minidisc; and 101a a center hole of the compact disc.

Let A be the dimension of one side of the housing 100c of the minidisc 100, B the clearance between the minidisc 100 and the compact disc 101, and C the dimension of the outside diameter of the compact disc 101, then the dimension D1 for arranging the minidisc 100 and the compact disc 101 in plane is $A+B+C$. The dimensions A and B are those determined in accordance with the standard ($A=72$ mm, $C=120$ mm). For example, when dimension B is set to 5 mm, dimension D1 needs to be ($D1=72$ mm+5 mm+120 mm) 197 mm.

The disc player for use in playback of both a minidisc and a compact disc to be mounted on vehicle cannot be mounted on a console box in almost all of vehicles unless they conform with the DIN Standard (West Germany Standard). For example, "1DIN size" set forth in the DIN Standard is 178 mm (width)×53 mm (height) in front panel size, which is outside the "1DIN size" in the above-described arrangement. Therefore, the disc player corresponding to the DIN Standard cannot be prepared.

The inventors of the present application have repeated their studies, and proposed the arrangement of the minidisc 100 and the compact disc 101 by making an optical pickup 103 for use in playback of both a minidisc and a compact disc the smallest dimension.

In FIG. 1B, the minidisc 100 and the compact disc 101 are arranged side by side on one and the same plane. In consideration that the minidisc 100 and the compact disc 101 are not used simultaneously, the pickup 103 provided between the minidisc 100 and the compact disc 101 is miniaturized to the smallest limit whereby the center holes 100a and 101a of the minidisc 100 and the compact disc 101 are brought close to each other so that the distance L1 between the centers in FIG. 1A is changed to the distance L2 between the centers in FIG. 1B.

Let E be the dimension where the minidisc 100 and the compact disc 101 overlap, then dimension D2 is $A+C-E$, which indicates the dimension shortened by B+E from the dimension D1 ($A+B+C$) shown in FIG. 1A. With this, D2 is the dimension of more or less 180 mm, which is however not within the "1DIN size".

SUMMARY OF THE INVENTION

A purpose of the present invention is to provide a compact disc player for use in playback of both a minidisc and a compact disc.

The present invention provides a disc player comprising: a first opening formed on a panel for loading a first disc storage medium with a first diameter; a second opening formed on the panel for loading a second disc storage medium with a second diameter longer than the first diam-

eter; a chassis provided in an orthogonal direction with respect to the panel; a turning frame horizontally turnably mounted on the chassis; a first rotary unit provided on the turning frame to rotate the first disc storage medium; a second rotary unit provided on the turning frame to rotate the second disc storage medium; and a rotary mechanism for horizontally turning the turning frame to move at least either the first or the second rotary unit to a predetermined information reading position.

Further, the present invention provides a disc player comprising: a first turntable on which a first disc storage medium with a first diameter is to be loaded; a second turntable on which a second disc storage medium with a second diameter longer than the first diameter is to be loaded; and a loading mechanism for loading the first and second disc storage media onto the first and second turntables, respectively; wherein the loading mechanism comprises: a first roller to transfer the second disc storage medium; a second roller to transfer the first disc storage medium, the second roller being provided as parallel to the first roller and within a lateral length of the first roller; a holder to hold the first disc storage medium, the holder being provided as close to the first turntable from the second roller; and an actuator to actuate the first and second rollers.

Further, the present invention provides a disc player comprising: a first opening formed on a panel for loading a first disc storage medium with a first diameter; a second opening formed on the panel for loading a second disc storage medium with a second diameter longer than the first diameter; a chassis provided in an orthogonal direction with respect to the panel; a turning frame horizontally turnably mounted on the chassis; a first rotary unit provided on the turning frame to rotate the first disc storage medium; a second rotary unit provided on the turning frame to rotate the second disc storage medium; a rotary mechanism for horizontally turning the turning frame to move at least either the first or the second rotary unit to a predetermined information reading position; and a loading mechanism for loading the first and second disc storage media onto the first and second rotary units, respectively; wherein the loading mechanism comprises: a first roller to transfer the second disc storage medium; a second roller to transfer the first disc storage medium, the second roller being provided as parallel to the first roller and within a lateral length of the first roller; a holder to hold the first disc storage medium, the holder being provided as close to the first turntable from the second roller; and an actuator to actuate the first and second rollers.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1A and 1B are plan views where a minidisc and a compact disc are arranged on a conventional disc player for use in playback of both a minidisc and a compact disc.

FIG. 2 is a perspective view showing an external appearance of a first embodiment of a disc player for use in playback of both a minidisc and a compact disc according to the present invention;

FIG. 3 is a view taken by an arrow X in FIG. 2;

FIGS. 4A and 4B illustrate a first operation of the disc player of FIG. 2 according to the present invention;

FIGS. 5A and 5B illustrate a second operation of the disc player of FIG. 2 according to the present invention;

FIG. 6 illustrates a third operation of the disc player of FIG. 2 according to the present invention;

FIG. 7 is a perspective view showing an external appearance of a second embodiment of a disc player for use in

playback of both a minidisc and a compact disc according to the present invention;

FIG. 8 is a plan view showing a clamp unit and a loading mechanism of the disc player of FIG. 7 according to the present invention;

FIG. 9 is a side view showing the clamp unit and the loading mechanism of FIG. 8 according to the present invention;

FIG. 10 is another side view showing the loading mechanism according to the present invention;

FIG. 11 is a side view showing essential portions of the loading mechanism according to the present invention;

FIG. 12 is a plan view showing a minidisc holder according to the present invention;

FIGS. 13A to 13C illustrate a first operation of the loading mechanism of the second embodiment according to the present invention;

FIGS. 14A to 14C illustrate a second operation of the loading mechanism of the second embodiment according to the present invention;

FIGS. 15A to 15E illustrate a third operation of the loading mechanism of the second embodiment according to the present invention;

FIGS. 16A to 16C illustrate a fourth operation of the loading mechanism of the second embodiment according to the present invention; and

FIGS. 17A and 17B illustrate a fifth operation of the loading mechanism of the second embodiment according to the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Preferred embodiments of the present invention will now be described in detail with reference to the accompanying drawings.

FIG. 2 shows an external appearance of a disc player 1 (recording and/or reproducing apparatus) for use in playback of both a minidisc (MD, a first disc storage medium) and a compact disc (CD, a second disc storage medium with a diameter longer than that of the first disc storage medium) as a first embodiment according to the present invention.

The disc player 1 is provided with a box-shaped casing 2, a front panel 3 mounted on the front surface of the casing 2, an upper cover 4 covering the upper surface of the casing 2, a floating chassis 5 as a chassis floatably mounted on the casing 2 in an orthogonal direction with respect to the panel 3, a mechanism unit 10 rotatably mounted on the floating chassis 5, and a rotary mechanism 30 for horizontally turning the mechanism unit 10.

The panel 3 is provided with a compact disc loading opening 7, and a minidisc loading opening 7a formed integral with a part of the compact disc loading opening 7. A central position Mo of the minidisc loading opening 7a is formed to be displaced by δ from a central position Co of the compact disc loading opening 7.

The floating chassis 5 is provided with a support 5a for supporting the mechanism unit 10 so that the unit 10 can be turned horizontally.

FIG. 3 is a view taken by an arrow X in FIG. 2, showing the plane of disc player 1 with the upper cover 4 of FIG. 2 removed.

The mechanism unit 10 is provided with a substantially rectangular-shaped turning frame 11; a rotary unit 12 for a minidisc, provided on the frame 11; a rotary unit 13 for a

compact disc, provided opposite to the rotary unit 12; an optical pickup 14 for use in playback of both a minidisc and a compact disc, movable between the rotary units 12 and 13; and a feed mechanism 15 for driving the pickup 14.

The turning frame 11 is provided with a hole 11a fitted into a support 5a of the floating chassis 5, and a cam groove 11b fitted into the rotary mechanism 30. The rotary unit 12 for a minidisc is provided with a motor 18 mounted on the turning frame 11, and a turntable 19 mounted on the motor 18. The rotary unit 13 for a compact disc is provided with a motor 21 mounted on the turning frame 11, and a turntable 22 mounted on the motor 21.

The feed mechanism 15 is provided with a feed motor 23 mounted on the turning frame 11, and a feed screw 25 for moving the pickup 14 connected to the feed motor 23 through a group of gears 24. The rotary mechanism 30 is provided with a motor 31 mounted on the floating chassis 5, a cam gear 33 connected to the motor 31 through a group of gears 32, and a transmission lever 34 for transmitting the movement of the cam gear 33 to the turning frame 11.

The cam gear 33 is provided with a gear 33a meshed with the group of gears 32, and a cam groove 33b fitted into the transmission lever 34. The transmission lever 34 is provided with a plate-like lever body 34a, a support 34b rotatably mounted on the floating chassis 5, a first pin 34c fitted into the cam groove 11b (as a cam follower), and a second pin 34d fitted into the cam groove 33b of the cam gear 33 (as a cam follower).

The motor 31 is driven to rotate the cam gear 33 through the group of gears 32, the transmission lever 34 is rotated by the second pin 34d fitted into the cam groove 33b of the cam gear 33, and the turning frame 11 is horizontally turned by the first pin 34c of the transmission lever 34.

Operations of the disc player 1 will be explained hereinafter.

FIGS. 4A and 4B illustrate the first operation of the disc player 1, showing a position of the mechanism unit 10 for reading or recording information of a minidisc 40.

The position of the mechanism unit 10 for reading or recording information of the minidisc 40 is also the position of the mechanism unit 10 in the initial state. When the minidisc 40 is loaded from the minidisc loading opening 7a as indicated by an arrow Y1, the minidisc 40 is detected by a detection switch not shown to maintain the initial state.

Since the minidisc 40 is controlled in the lateral position with respect to the panel 3 by the minidisc loading opening 7a, the position of the minidisc 40 coincides with that of the turntable 19 in the lateral direction.

FIGS. 5A and 5B illustrate the second operation of the disc player 1, showing a position of the mechanism unit 10 for reading information of a compact disc 50.

When the compact disc 50 is loaded from the compact disc loading opening 7 as indicated by arrows Y2, the compact disc 50 is detected by a detection switch not shown. The motor 31 is driven to rotate the cam gear 33 through the group of gears 32 as indicated by an arrow Y3, and the transmission lever 34 is rotated as indicated by an arrow Y4 by the second pin 34d fitted into the cam groove 33b of the cam gear 33. The rotary frame 11 is rotated as indicated by an arrow Y5 about the support 5a of the floating chassis 5 by the first pin 34c of the transmission lever 34, and a read position on the compact disc 50 is moved to a substantially central position of the compact disc 50 loading opening 7. This achieves miniaturization of disc player 1 for use in playback of both a minidisc and a compact disc.

The compact disc **50** is loaded from the inserting opening **7** and thereby subjected to centering onto the turntable **22** by a centering mechanism not shown.

FIG. **6** illustrates the third operation of the disc player **1**, showing the comparison of the spacing between a case where the turning frame **11** is rotated to a predetermined position in order to read information on the compact disc **50** and another case where the turning frame **11** is not rotated.

Positions of the turntable **22** and the compact disc **50** when the turning frame **11** has been rotated to the predetermined position are shown by the dash-dotted contour lines. A position of the turntable **22** when the turning frame **11** has not been rotated is shown by the broken lines, and a position of the compact disc **50** when the turning frame **11** has not been rotated is shown by the solid line.

The position of the compact disc **50** where the turning frame **11** has been rotated to the predetermined position is substantially in the central position with respect to the loading opening **7** of the compact disc **50**, whereas the position of the compact disc **50** where the turning frame **11** has not been rotated is close to the right as viewed in the drawing with respect to the loading opening **7** and is therefore outside the minidisc **40** and the disc player **1**.

That is, since the turning frame **11** is rotatable to the predetermined position as indicated by arrow **Y6**, the disc player **1** can be miniaturized by dimension **F** laterally of the panel **3**. Thereby, the disc player for use in playback of both a minidisc and a compact disc or use on vehicles in conformity with the DIN standard can be achieved.

A second embodiment according to the present invention will be described. Elements in this embodiment that are the same as or analogous to elements in the foregoing embodiment are referenced by the same reference numerals and will not be explained in detail.

FIG. **7** shows an external appearance of a disc player **1a** also for use in playback and/or recording of both a minidisc (MD, a first disc storage medium) and a compact disc (CD, a second disc storage medium with a diameter longer than that of the first disc storage medium) according to the present invention.

In addition to the elements shown in FIG. **2**, the disc player **1a** of FIG. **7** is provided with a clamp unit **400** and a loading mechanism **500**. The clamp unit **400** clamps a minidisc (MD) cartridge containing a minidisc. The loading mechanism **500** loads a compact disc or a minidisc into the disc player **1a** through the compact disc loading opening **7** or the minidisc loading opening **7a**.

The clamp unit **400** and the loading mechanism **500** are explained with reference to FIGS. **8**, **9** and **10**.

The clamp unit **400** is provided with a clamp holder **41** rotatably (within a specific angle) attached at its one end to the floating chassis **5**; a flat spring **42** attached to the other end of the clamp holder **41**; a clamper **43** rotatably attached to the flat spring **42**; extension springs **44** bridged over the upper cover **4** and the clamp holder **41**; and an actuator (not shown) for actuating the clamp holder **41**.

The loading mechanism **500** is provided with a first roller unit **51** rotatably attached to the floating chassis **5**; a second roller unit **52** rotatably attached to the first roller unit **51**; an actuator **53** for rotating the roller units **51** and **52**; a rotary lever (level adjuster) connected to the first roller unit **51**; and a minidisc holder **90** located close to the turntable **19** from the second roller unit **52**.

The first roller unit **51** is provided with a first roller frame **56** rotatably (within a specific angle) attached to the floating

chassis **5**; a first roller **57** rotatably provided between side plates of the first roller frame **56**; and a transmission shaft unit **58** rotatably attached to the first roller frame **56**.

The first roller frame **56** is provided with intermediate gears **59** and **61** linked to the transmission shaft **58** and a reversal spring **62** bridged over the first roller frame **56** and the floating chassis **5**. The first roller frame **56** is formed with a hole **56a** for connection to the second roller unit **52**. Supporters **56b** support the first roller frame **56** as rotatably attached to the floating chassis **5**.

The first roller **57** is provided with a roller shaft **63**; a long rubber roller **64** with a concave middle portion rotatably attached to one end of the roller shaft **63**; a free roller **65** rotatably attached to the rubber roller **64** at one end thereof, with a slightly larger diameter than that of an end portion of the rubber roller **64**; and a final gear **66** attached to the other end of the roller shaft **63**. The first roller **57** is long enough to transfer a large compact disc with a diameter of 12 cm.

The transmission shaft unit **58** includes a shaft **68**; a drive gear **69** attached to the shaft **68**; and transmission gears **71** and **72** attached to both ends of the shaft **68**.

The second roller unit **52** is located inside the first roller frame **56**. The second roller unit **52** is provided with a second roller frame **73** rotatably attached to the shaft **68** via collar (not shown); a second roller **74** rotatably provided between left and right side plates of the second roller frame **73**; and a hinge lever **75** for leaping up the second roller frame **73**. The second roller **74** is short enough to transfer an MD cartridge and provided as parallel to the first roller **57** within a lateral length thereof.

The second roller frame **73** has an intermediate gear **77** linked to the transmission shaft **58** via the transmission gear **72**. A protrusion **73a** is fitted into the hole **56a** of the first roller frame **56**. The hinge lever **75** is fitted in a groove **73b**.

The second roller **74** is provided with a roller shaft **79**; a resin roller **81** attached to the roller shaft **79**; a rubber roller **82** by which the resin roller **81** is partially covered from an end thereof; and a final gear **83** attached to an end of the roller shaft **79** at rubber roller side.

The hinge lever **75** is provided with a shaft **75a** rotatably attached to the first roller frame **56**; a lever **75b** operated by loading an MD cartridge; and an operating portion **75c** for leaping up the second roller frame **73**.

A torsion spring **85** is bridged over the lever **75b** and the first roller frame **56**, for returning back the hinge lever **75** to its initial position.

The actuator **53** is provided with a motor **86** attached to the floating chassis **5**; a worm gear **87** attached to a shaft **86a** of the motor **86**; and a link gear **88** engaged with the worm gear **87**. The link gear **88** is further engaged with the drive gear **69**.

The disc player **1a** is provided with only one actuator **53** for actuating both the first roller **57** for transferring a compact disc and the second roller **74** for transferring an MD cartridge.

The second roller **74** is shorter than the first roller **57** and provided therealong for compactness and lightness of the loading mechanism **500**.

The loading mechanism **500** is explained with reference to FIG. **10**.

The rotary lever **54** is provided with a U-groove **54a** in which the roller shaft **63** is fitted; a pivot **54b** rotatably attached to the floating chassis **5**; and a drive pin **54c** fitted in an actuator (not shown). The supporters **56b** for rotatably supporting the first roller frame **56** and the shaft **68** for rotatably supporting the second roller frame **73** are arranged coaxially.

Lateral slide of the drive pin 54c in a direction indicated by an arrow A by the actuator (not shown) rotates the rotary lever 54 around the pivot 54b. Rotation of the rotary lever 54 makes the first roller frame 56 turn around the pivot 54b with the second roller frame 73 in a direction indicated by an arrow B to be displaced by means of the reversal spring 62 as indicated by a chain double-dashed line.

The relationship between the second roller frames 56 and 73 and the hinge lever 75 is explained with reference to FIG. 11.

FIG. 11 depicts the second roller frame 73 rotatably attached to the transmission shaft 58 via collar (not shown) and the protrusion 73a fitted in the hole 56a.

The operating portion 75c is fitted in the groove 73b and turns around the shaft 75a in a counter clockwise direction by a force applied to the lever 75b in a direction indicated by an arrow D. Rotation of the operating portion 75c makes the second roller frame 73 to turn around the shaft 68 in a direction indicated by an arrow E. The second roller frame 73 thus leaps up to touch the hole 56a at its protrusion 73a to let the first roller frame 56 leap up. Release of the force applied in the direction of arrow D makes the first roller frame 56 return to its initial position with the torsion spring 85 bridged over the lever 75b and the first roller frame 56.

The minidisc holder 90 is explained with reference to FIG. 12.

The minidisc holder 90 includes a holder 91 and a shutter operating unit 92 rotatably attached to the holder 91.

The holder 91 is provided with a supporting shaft 91a of the shutter operating unit 92; side guides 91b and 91c for guiding side faces of an MD cartridge; and front guides 91d and 91e for smooth loading of the MD cartridge.

The shutter operating unit 92 is provided with an operating holder 93 rotatably (within a predetermined range) attached to the supporting shaft 91a; a shutter operating spring 94 attached to the operating holder 93; and a torsion spring 95 bridged over the holder 91 and the operating holder 93. The operating holder 93 has a lock release 93a for an MD cartridge and a hole 93b for accepting the supporting shaft 91a.

A first operation of the loading mechanism 500 is explained with reference to FIGS. 13A to 13C.

FIG. 13A illustrates a state in that an MD cartridge M can be loaded into the disc player 1a only through the minidisc loading opening 7a not the compact disc opening 7.

FIG. 13B illustrates a state in that the mechanism unit 10 is positioned where the MD cartridge M can be loaded into the disc player 1a. FIG. 13B further illustrates a state in that lateral positions of the MD cartridge M and the turntable 19 meet each other by restriction of lateral position of the MD cartridge M through the minidisc loading opening 7a with respect to the front panel 3 as described in the first embodiment.

FIG. 13C illustrates a state in that the MD cartridge M has been loaded just in front of the loading mechanism 500.

A second operation of the loading mechanism 500 is explained with reference to FIGS. 14A to 14C.

FIG. 14A illustrates a state in that loading of the MD cartridge M in a direction indicated by an arrow Z1 operates the hinge lever 75 (FIG. 11) to leap up the second roller unit 52 to push the first roller unit 51 upward with the protrusion 73a of the second roller unit 52.

Loading of the MD cartridge M into the disc player 1a to a predetermined position is detected by a detection switch (not shown) to rotate the first roller 57 in a direction

indicated by an arrow Z2 while the second roller 74 in the opposite direction indicated by an arrow Z3.

The first and second rollers 57 and 74 always rotate in opposite directions due to difference in construction such that the first roller unit 51 has the two intermediate gears 59 and 61, whereas the second roller unit 52 only one intermediate gear 77 as shown in FIG. 8.

FIG. 14B illustrates a state in that the second roller 74 touches the upper surface of the MD cartridge M to transfer the MD cartridge M in a direction of the turntable 19. The MD cartridge M is further transferred in a direction indicated by an arrow Z4 while pushing the second roller 74 upward. The first roller 57 rotates in the opposite direction with respect to the second roller 74. However, the transfer of the MD cartridge M is free from the existence of the first roller 57 due to the construction in that the first roller 57 has a free roller 65 touching the upper surface of the MD cartridge M.

FIG. 14C illustrates a state in that the second roller 74 is stopped after the transfer of the MD cartridge M to the predetermined position to operate the rotary lever 54 for chucking the MD cartridge M on the turntable 19 and rotate the clamp unit 400. The MD cartridge M is clamped by the second roller 74 and the clasper 43 via the rotary lever 54 and the first roller 57. The second roller 74 functions as a clasper after the transfer of the MD cartridge M to the predetermined position due to the construction such that the second roller 74 is attached to the floating chassis 5 side via the first roller 57 and the rotary lever 54 as a level adjuster.

A third operation of the loading mechanism 500 is explained with reference to FIGS. 15A to 15E illustrating a shutter opening operation of the MD cartridge M while transferred.

As shown in FIG. 15A, the MD cartridge M has a housing M1 and a shutter M2 slidably attached to the housing M1. The housing M1 includes a shutter release groove M3 for releasing locking of the shutter M2 and a lock button M4 attached to the shutter release groove M3. The shutter M2 is formed with a hole M5 for transferring the shutter M2.

FIG. 15A illustrates a state in that loading the MD cartridge M into the holder 91 in a direction indicated by an arrow Z5 makes one end of the housing M1 touch the lock release 93a.

FIG. 15B illustrates a state in that further loading of the MD cartridge M into the holder 91 makes the one end of the housing M1 push the lock release 93a to rotate in a direction indicated by an arrow Z6.

FIG. 15C illustrates a state in that still further loading of the MD cartridge M into the holder 91 makes the shutter operating unit 92 became parallel to a direction in which the MD cartridge M has been loaded, the lock release 93a being fitted in the shutter release groove M3.

FIG. 15D illustrates a state in that more further loading of the MD cartridge M into the holder 91 makes the lock release 93a push the lock button M4 and the shutter operating spring 94 be fitted in the hole M5 of the shutter M2.

FIG. 15E illustrates a state in that loading of the MD cartridge M into the holder 91 to a predetermined position opens the shutter M2.

The present invention achieves the loading mechanism 500 compact in a depth direction by means of the rotatable shutter operating unit 92 that is pushed upward by the MD cartridge M in use, whereas set at a waiting position while not being used.

A fourth operation of the loading mechanism 500 is explained with reference to FIGS. 16A to 16C illustrating a

compact disc C loaded into the disc player 1a through the compact disc loading opening 7 on the panel 3.

FIG. 16A illustrates a state in that the compact disc C can be loaded into the disc player 1a through the compact disc loading opening 7.

FIG. 16B illustrates a state in that the loaded compact disc C is detected by the detection switch (not shown) to make the rotary mechanism 30 to rotate the mechanism unit 10 to a predetermined position as described in the first embodiment.

FIG. 16C illustrates a state in that the compact disc has been loaded just in front of the loading mechanism 500.

A fifth operation of the clamp unit 400 and of the loading mechanism 500 is explained with reference to FIGS. 17A and 17B.

FIG. 17A illustrates a state in that the first roller 57 rotates in a direction indicated by an arrow Z7 to touch the lower surface of the compact disc C to transfer the disc C in a direction indicated by an arrow Z8. The transfer of the compact disc C is free from the existence of the second roller 74 due to the construction such that the second roller 74 is lower than the first roller 57 from the lower surface of the compact disc C even though the second roller 74 rotates in a direction indicated by an arrow Z9 opposite to a rotary direction of the first roller 57.

FIG. 17B illustrates a state in that after the transfer of the compact disc C to a predetermined position, the rotary lever 54 chucks the compact disc C on the turntable 22 and the clamp unit 400 is rotated to clamp the compact disc C.

A small compact disc of 8 cm-diameter also can be transferred by the first roller 57 through processes described with reference to FIGS. 16A to 16C and 17A and 17B.

The first and second roller units 51 and 52 are not only provided as rotatable as a level adjuster but may be slidable in a vertical direction.

According to the present invention, a disc player is formed with an opening formed on a panel for loading a minidisc and another opening formed on the panel for loading a compact disc with a diameter longer than that of the minidisc. A chassis is provided in an orthogonal direction with respect to the panel. Mounted on the chassis is a turning frame that is horizontally turnable on the chassis. Provided on the turning frame are a first rotary unit for rotating the minidisc and a second rotary unit for rotating the compact disc. The turning frame is turned horizontally to move at least either the first or the second rotary unit to a predetermined information reading position.

This configuration enables the miniaturization of the disc player for use in playback of both a minidisc and a compact disc.

The miniaturization of the disc player is further achieved by the arrangement such that a central position of the minidisc loading opening is displaced from another central position of the compact disc loading opening, and the turning frame is horizontally turned so that reading positions of the minidisc and the compact disc correspond to the substantially central positions of the respective loading openings.

Further, according to the present invention, the disc player has a first and a second turntable on which the minidisc and the compact disc are loaded, respectively, by a loading mechanism. The loading mechanism has a first roller to transfer the compact disc and a second roller the minidisc. The second roller is provided as parallel to the first roller and within a lateral length of the first roller. The minidisc is held

by a holder provided as close to the first turntable from the second roller. The present invention achieves one actuator for rotating the first and second rollers.

Further, the present invention achieves the loading mechanism compact in a depth direction by means of the rotatable shutter operating unit that is pushed upward in use by an MD cartridge M containing the minidisc in use, whereas set at a waiting position while not being used.

Further, the present invention achieves the second roller for transferring the minidisc functioning as a clasper to clamp a disc cartridge containing the minidisc on the first turntable side by an arrangement in that the second roller is rotated by the actuator to touch an upper surface of the disc cartridge with respect to the turntable while the disc cartridge is being loaded, the second roller being stopped to rotate after completion of the disc cartridge loading.

Further, the present invention achieves perfect clamping of the disc cartridge by clamping the upper surface of the disc cartridge by the clasper and the second roller.

What is claimed is:

1. A disc player comprising:

- a first opening formed on a panel for loading a first disc storage medium with a first diameter;
- a second opening formed on the panel for loading a second disc storage medium with a second diameter longer than the first diameter;
- a chassis provided in an orthogonal direction with respect to the panel;
- a turning frame mounted on the chassis and horizontally turnable between two predetermined positions;
- a first rotary unit provided on the turning frame to rotate the first disc storage medium;
- a second rotary unit provided on the turning frame to rotate the second disc storage medium; and
- a rotary mechanism for horizontally turning the turning frame to move at least either the first or the second rotary unit to a predetermined information reading position.

2. The disc player according to claim 1, wherein a central position of the first loading opening is displaced from a central position of the second loading opening, and the turning frame is horizontally turnable so that reading positions on the first and the second disc storage medium correspond to substantially central positions of the first and second loading openings, respectively.

3. The disc player according to claim 1 further comprising an optical pickup provided on the turning frame and movable between the first and the second rotary unit to read information on the first and the second disc storage medium.

4. The disc player according to claim 1, wherein the first disc storage medium is a minidisc and the second disc storage medium is a compact disc.

5. A disc player comprising:

- a first turntable on which a first disc storage medium with a first diameter is to be loaded;
- a second turntable on which a second disc storage medium with a second diameter longer than the first diameter is to be loaded; and
- a loading mechanism for loading the first and second disc storage media onto the first and second turntables, respectively;

wherein the loading mechanism comprises:

- a first roller to transfer the second disc storage medium;
- a second roller to transfer the first disc storage medium, the second roller being provided as parallel to the first roller and within a lateral length of the first roller;

11

a holder to hold the first disc storage medium, the holder being provided as close to the first turntable from the second roller; and

an actuator to actuate the first and second rollers.

6. The disc player according to claim 5, wherein the minidisc holder includes a shutter opening unit to open a shutter of a disc cartridge containing the first disc storage medium, the shutter opening unit being rotatable for being pushed in a predetermined direction while the disc cartridge is being loaded whereas being set at a waiting position while the disc cartridge is not loaded.

7. The disc player according to claim 5, wherein the second roller is rotated by the actuator to touch an upper surface of a disc cartridge containing the first disc storage medium with respect to the first turntable while the disc cartridge is being loaded, the second roller being stopped to rotate after completion of the disc cartridge loading, the second roller thus clamping the disc cartridge on the turntable side.

8. The disc player according to claim 5 further comprising a clamper, the second roller and the damper clamping an upper surface of a disc cartridge containing the first disc storage medium with respect to the first turntable while the disc cartridge is being loaded.

9. The disc player according to claim 5, wherein the first disc storage medium is a minidisc and the second disc storage medium is a compact disc.

10. A disc player comprising:

a first opening formed on a panel for loading a first disc storage medium with a first diameter;

12

a second opening formed on the panel for loading a second disc storage medium with a second diameter longer than the first diameter;

a chassis provided in an orthogonal direction with respect to the panel;

a turning frame horizontally turnably mounted on the chassis;

a first rotary unit provided on the turning frame to rotate the first disc storage medium;

a second rotary unit provided on the turning frame to rotate the second disc storage medium;

a rotary mechanism for horizontally turning the turning frame to move at least either the first or the second rotary unit to a predetermined information reading position; and

a loading mechanism for loading the first and second disc storage media onto the first and second rotary units, respectively;

wherein the loading mechanism comprises:

a first roller to transfer the second disc storage medium; a second roller to transfer the first disc storage medium, the second roller being provided as parallel to the first roller and within a lateral length of the first roller;

a holder to hold the first disc storage medium, the holder being provided as close to the first turntable from the second roller; and

an actuator to actuate the first and second rollers.

* * * * *